







AIR COOLED



## 1.5 Ton **Portable** Air Conditioner

## **Product Features:**

- 24V Control Circuit with Non-Programmable Electronic Thermostat
- Swivel Ball Bearing Casters with Locking Fronts
- 2-Speed Fan Switch
- Condensate Overflow Alert Light
- · High Pressure Safety Switch
- Washable Electrostatic Air Filters

## **Technical Specifications:**

Specifications subject to change without notice

Cooling Capacity: 16,800 BTUH 115V, 60Hz, 1PH Voltage:

Amps: 14.1 Total Watts: 1670

Operating Range Cooling Ambient:

65° to 105°

Outdoor Use: No

Cooling Capacity: Total BTUH at 80°DB/67°WB

Return Air 95°F Outdoor

at High Fan Speed.

In Rush Amps: 75

Depth:

Net Weight:

Plug Type: 5-20P, LCDI EER:

10.0

NOTE: Dedicated circuit and time delay fuses / circuit breakers are recommended.

Compressor: Rotary 1 1/2 Compressor HP: 63 Compressor LRA: EVAP CFM - High: 600 EVAP Motor HP: 1/8 COND CFM 930 COND MOTOR HP 1/8 Condensate Tank: 5 Gallon Pump Optional Refrigerant Charge: 40 oz R-410A Height: 46.7" Width: 24" 29.5"

260 lbs.





## **Optional Accessories**



Ceiling Panel Kit
For discharging the condenser air above a drop ceiling
Part Number: CK-12



Nozzle Kit / 2 x 6" For directional cooling Part Number: 2NK-2



Evaporator Return Air Plenum For ducting return air Part Number: 2002



**Discharge Duct Adapter**For extended duct length
Part Number: 2DDA-80



**Universal Condensate Pump Kit**For unattended operation
Part Number: UPK-115



Condenser Return Air Plenum
For installations where it is required to duct air to the inlet of the condenser.
Part Number: 2DCP-2



